

02-24-00

A

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))	Attorney Docket No.	Bancal-8
	First Inventor or Application Identifier	Bancal
	Title	Flat Display Screen Resistive Anode
	Express Mail Label No.	EJ596854523

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing) 2. <input checked="" type="checkbox"/> Specification [Total Pages 16] (preferred arrangement set forth below) - Descriptive title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 2] 4. Oath or Declaration [Total Pages 3] a. <input type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 16 completed) i. <input type="checkbox"/> <u>DELETION OF INVENTOR(S)</u> Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	5. <input type="checkbox"/> Microfiche Computer Program (Appendix) 6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies
ACCOMPANYING APPLICATION PARTS	
7. <input type="checkbox"/> Assignment Papers (cover sheet & document(s)) 8. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement <input type="checkbox"/> Power of Attorney (when there is an assignee) 9. <input type="checkbox"/> English Translation Document (if applicable) 10. <input checked="" type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input checked="" type="checkbox"/> Copies of IDS Citations 11. <input checked="" type="checkbox"/> Preliminary Amendment 12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 13. <input type="checkbox"/> * Small Entity Statement filed in prior application, Status still proper and desired (PTO/SB/09-12) 14. <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 15. <input type="checkbox"/> Other:	

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____
 Prior application information: Examiner _____ Group / Art Unit: _____
 For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label ☒ Correspondence address below
 (Insert Customer No. or Attach bar code label here)

Name	Arthur L. Plevy				
	BUCHANAN INGERSOLL, P.C.				
Address	650 College Road East, 4th Floor				
City	Princeton	State	NJ	Zip Code	08540
Country	US	Telephone	609-987-6880	Fax	609-520-0360

Name (Print/Type)	Paul A. Schwarz	Registration No. (Attorney/Agent)	37,577
Signature	<i>Paul A. Schwarz</i>	Date	2/23/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

"EXPRESS MAIL CERTIFICATE"

"Express Mail" mailing label number: EJ596854523US

Date of Deposit: February 23, 2000


Title of Invention: FLAT DISPLAY SCREEN RESISTIVE ANODE

Inventor: BANCAL, Bernard; OLIVIER, Pascal

Type of Documents:

1. Utility Patent Application Transmittal;
2. Fee Transmittal for FY 1999;
3. Application consisting of 14 pages of specification, 1 page of claims, 1 page of abstract, and 2 pages of drawings;
4. Preliminary Amendment;
5. Declaration and Power of Attorney (unexecuted);
6. Information Disclosure Statement;
7. PTO - Form 1449;
8. IDS References;
9. Our check in the amount of \$690.00;
10. Acknowledgment Postcard; and,
11. "Express Mail" Certificate.

I hereby certify that this paper and fee are being deposited with the United States Postal Service's "Express Mail Post Office to Addressee" service under 37 CFR §1.10 on the date indicated above and is addressed to Assistant Commissioner for Patents, "Box Application," Washington, D.C. 20231.



Tammy T. Fattoross

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Patent Application of:	:	Group Art Unit: TBA
BANCAL <i>et al.</i>	:	
	:	
Serial No.: Herewith	:	Examiner: TBA
	:	
Filing Date: Herewith	:	Date: February 23, 2000
	:	
For: FLAT DISPLAY SCREEN	:	
RESISTIVE ANODE	:	
.....	:	

Assistant Commissioner of Patents
Washington, DC 20231

PRELIMINARY AMENDMENT

Dear Sir:

Preliminary to the first Official Action in the above-captioned application, please amend the same as follows:

IN THE CLAIMS

Please amend the following claims:

6.(AMENDED) The anode of [any of claims 1 to 5] claim 1, wherein the resistive layer (8, 8', 8'') is not patterned.

7.(AMENDED) The anode of [any of claims 3 to 5] claim 3, wherein the resistive layer (8'') has the same pattern as the reflective layer (10).

8.(AMENDED) The anode of [any of claims 1 to 7] claim 1, wherein the resistive layer (8) has, at least in the active screen area, the same pattern as the biasing conductive layer (5).

9.(AMENDED) The anode of [any of claims 1 to 8] claim 1, wherein said conductive layer has a pattern of alternate strips (5R, 5G, 5B) interconnected in at least two sets.

Please cancel claim 10.

Please add the following claim:

11.(NEW) A flat display screen including:

a cathodoluminescent anode (2) having phosphor elements (4R, 4G, 4B, 4'R, 4'G, 4'B) intended for being excited by an electron bombardment, these elements being deposited on at least one biasing electrode including, at least under the phosphor elements, a resistive layer (8, 8', 8'') deposited on a conductive layer (5B, 5R, 5G) for biasing the phosphor elements; and

a cathode (1) for generating electrons bombarding the anode.

STATUS OF THE CLAIMS

Claims 1-10 are pending. Claims 6-9 has been amended herein, claim 10 has been cancelled herein, and claim 11 has been added herein.

REMARKS

Claims 6, 8, and 9 each have been amended to depend only from claim 1, and claim 7 has been amended to depend only from claim 3 only. Claim 10 has been cancelled and rewritten as

new claim 11 in order to comply with U.S. practice.

No fees are believed due as a result of this Preliminary Amendment. The Commissioner is hereby authorized to charge any other fees which may be required, or credit any overpayment, to Deposit Account number 50-1057.

Respectfully submitted,



Paul A. Schwarz, Esq.
Reg. No. 37,577

BUCHANAN INGERSOLL, P.C.
650 College Road East, 4th Floor
Princeton, New Jersey 08540
(609) 987-6883
(609) 520-0360 - facsimile

FLAT DISPLAY SCREEN RESISTIVE ANODE

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a flat display screen anode having phosphors excited by electrons, for example, of microtip type. It more specifically relates to the biasing of phosphor elements of an anode provided with phosphor elements of different colors biased per color, for example, alternate strips of phosphor elements organized in combs.

Discussion of the Related Art

Fig. 1 very schematically shows the structure of a flat microtip screen of the type to which the present invention relates. This screen is comprised of two plates. A first plate 1, currently called the cathode plate, is arranged to face a second plate 2, currently called the anode plate. The two plates are spaced apart from each other by spacers 3 regularly distributed in the screen surface, and a vacuum is created in the area defined by the two plates and a peripheral sealing joint 4.

Cathode plate 1 includes electron generation elements and pixel selection elements (not shown) that may be organized in different ways, for example, as described in US patent n° 4,940,916 of the Commissariat à l'Energie Atomique in the case of microtip screens. Anode plate 2 is, in the case of a color

screen, provided with alternate strips of phosphor elements, each strip corresponding to a color (red, green, blue).

Figs. 2A and 2B very schematically show a front view and a cross-section view of a portion of an anode plate. In Fig. 2B, the surface corresponding to the internal screen surface faces up. The anode includes, for example, alternate strips 4R, 4G, 4B of respectively red, green, blue phosphor elements. As illustrated in Fig. 2B, the strips of phosphor elements are arranged on corresponding conductive strips 5R, 5G, 5B generally organized in combs, all strips 5R being interconnected, as well as all strips 5G and all strips 5B. In certain cases, the phosphor elements are distributed in elementary patterns, each of which generally corresponds to a pixel (in fact, a sub-pixel of each color for a trichromatic screen). The "pixelized" phosphor elements can then still be addressed by biasing electrodes in conductive strips (5G, 5B and 5R) such as described in relation with Figs. 2A and 2B, but a specific mask is used to deposit the phosphor elements.

Two great categories of flat screens can be distinguished according to whether the user looks at the screen from the anode side or from the cathode side. In the first case, the light emitted by the phosphor elements propagates through the anode plate (downwards in Fig. 2B). The material of conductive strips 5R, 5G, 5B then is transparent, currently indium and tin oxide (ITO). In the second case, transparent electrodes 5R, 5B, 5G are replaced with opaque and preferably reflective electrodes, so that the largest possible part of the light emitted by phosphor elements 4R, 4G, 4B is sent back to the cathode once the phosphors have been excited by an electron bombardment. Electron generating plate 1 then is at least partially transparent and the observation is performed through this cathode plate.

In a color screen (or in a monochrome screen formed of two alternate sets of strips of phosphor elements of same color), the sets of strips (for example, blue, red, green) are often alternately positively biased with respect to cathode 1, so that

the electrons extracted from the emissive elements (for example, the microtips) of a pixel of the cathode are alternately directed towards phosphor elements 4R, 4G, 4B facing each of the colors.

5 The selection control of the phosphor that is to be
bombarded by the electrons imposes controlling, respectively, the
biasing of the phosphor elements of the anode, color by color.
Generally, the strips 5R, 5G, 5B supporting phosphor elements to
be excited are biased under a voltage of several hundreds of
volts with respect to the cathode, the other strips being at a
10 zero potential. The choice of the values of the biasing poten-
tials is linked to the characteristics of the phosphor elements
and of the emissive means.

15 In some cases, the anode may, while being formed of
several sets of phosphor elements or the like, not be switched by
sets of strips. All strips are then biased to a same potential,
at least for the duration of a display frame. The anode is then
said to be unswitched.

20 The potential difference between the anode and the
cathode is essentially due to the inter-electrode distance, that
is, to the thickness of the internal space. A maximum potential
difference is desired for reasons of display brightness, which
results in searching the greatest possible inter-electrode
distance. However, the structure of the inter-electrode space,
that includes spacers 3 likely to create dark areas in the screen
25 if their size is too large, prevents from increasing this inter-
electrode distance.

30 The necessary trade off leads to choosing an anode-
cathode voltage value that is critical from the point of view of
electric arc formation. Destructive electric arcs can then be
caused by the smallest dimensional irregularity of the distance
separating an emissive means of the cathode from the phosphor
elements of the anode. Such irregularities are, moreover, inevi-
table given the small dimensions and the techniques used to form
the anode and the cathode.

On the cathode side, a resistive layer is provided in the case of microtip screens to receive the microtips and thus limit the formation of destructive short-circuits between the microtips and a control grid associated with the cathode.

5 Conversely, on the anode side, arcs may occur not only between the cathode plate and those of the anode phosphor elements that are biased to attract electrons emitted by the microtips, but also between two neighboring strips of phosphor elements, due to the potential difference between the two strips.

10 In the case of a monochrome screen where the anode is formed of a conductive plane supporting phosphor elements of same color or in the case of an anode (color or monochrome) with several unswitched strips, the risk of arcs only exists between the anode and the cathode.

15 To limit the occurrence of such lateral arcs, it is currently provided to arrange, between anode strips 5B, 5R, 5G, interstitial strips 7 made of an insulating material (generally silicon oxide).

20 However, in practice, the efficiency of such insulating strips is limited for several reasons.

First, these strips are inoperative with respect to the forming of electric arcs between the anode and the cathode.

25 Further, and although this does not necessarily appear in Figs. 2A and 2B in which the scales have not been respected, phosphor elements 4R, 4G, 4B significantly extend beyond the interstitial strips. Indeed, the thickness of the strips of phosphor elements is generally on the order of some ten μm and the forming of silicon oxide insulating strips of such a thickness is, in practice, incompatible with the technologies

30 used for manufacturing the anodes, so that the thickness of strips 7 generally is on the order of 1 to 2 μm , their width being on the order of 10 to 20 μm .

35 Further, during the deposition of the phosphor elements through a deposition mask, a slight misalignment of the mask may occur, so that a portion of conductive strips 5R, 5G, 5B or of

the insulated areas becomes accessible once the screen is completed and thus favors the forming of arcs.

A first known solution to attempt to reduce the forming of arcs between the anode and the cathode is to provide, at the
5 end of each conductive strip 5R, 5G, 5B, a resistor between the power supply line and the strip. As soon as a strong current appears in the strip, the resistor causes a voltage drop. As a result, the potential difference between the conductive strip and the cathode decreases and has the overvoltage generating the arc
10 disappear.

A disadvantage of such a solution is that it does not protect from the forming of a lateral electric arc, that is, an arc between two neighboring strips 5R, 5G, 5B. A local current circulation may indeed occur between two strips, which is then
15 not prevented by the end resistors.

Another disadvantage of using such resistors in series with the strips is that the resistors are generally made of ruthenium, the resistivity of which is stabilized by anneal. This anneal at high temperature (on the order of 600°C) necessary to
20 stabilize the resistor raises problems of compatibility with the screen manufacturing process that requires, for the case where the conductive strips are made of aluminum in the case of a transparent anode, temperatures under 600°C. Further, such a manufacturing method by anneal is difficult to control.

Another disadvantage of series resistors interposed between the anode conductive strips is that they form heating areas for the anode conductive tracks at the screen periphery.

A second known solution is described in French patent application n° 2,732,160. This solution consists of depositing
30 the strips of phosphor elements on strongly resistive strips and bringing the biasing necessary to the phosphors by lateral biasing strips on either side of each resistive strip.

Even though this solution can provide satisfactory results, it requires a significant space between each strip of
35 phosphor elements to house therein two biasing conductors

respectively associated with two neighboring strips while sufficiently separating these biasing conductors from each other to maintain a necessary lateral insulation between them. Thus, this solution is, in practice, more particularly intended for
 5 screens of low resolution.

Conversely and as an example, for an anode plate in which the surface of each pixel is a square having a side of approximately 300 μm , the anode strips each have a neighboring width, but under 100 μm , and insulating strips 7 have a width on
 10 the order of some ten μm . In such a case, the implementation of a solution of local protection by a resistive layer laterally surrounded by biasing strips cannot be envisaged due to the small distance between anode strips.

Summary of the invention

The present invention aims at overcoming the disadvantages of conventional techniques by providing a flat display
 15 screen anode that suppresses the risk of occurrence of an electric arc between the anode and the cathode plate, or between two neighboring strips of phosphor elements of the anode, without adversely affecting the screen brightness.

20 The present invention also aims at providing a solution that is compatible with conventional distances between two strips of phosphor elements.

The present invention also aims at providing a solution that is particularly adapted to a "transparent" cathode screen,
 25 that is, the cathode plate of which forms the screen display surface.

The present invention further aims at providing a solution that respects conventional anode manufacturing methods and, in particular, the masks used in this manufacturing.

30 To achieve these objects, the present invention provides a flat display screen anode, including phosphor elements intended for being excited by an electron bombarding, these elements being deposited on at least one biasing electrode including, at least under the phosphor elements, a resistive

layer deposited on a conductive layer for biasing the phosphor elements.

According to an embodiment of the present invention, the phosphor elements are directly deposited on the resistive layer.

According to an embodiment of the present invention, the phosphor elements are deposited on a reflective conductive layer, itself deposited on the resistive layer.

According to an embodiment of the present invention, the reflective layer is deposited according to elementary patterns of small dimension in the anode surface.

According to an embodiment of the present invention, the phosphor elements are deposited according to the elementary pattern of deposition of the reflective layer.

According to an embodiment of the present invention, the resistive layer is not patterned.

According to an embodiment of the present invention, the resistive layer has the same pattern as the reflective layer.

According to an embodiment of the present invention, the resistive layer has, at least in the active screen area, the same pattern as the biasing conductive layer.

According to an embodiment of the present invention, said conductive layer has a pattern of alternate strips interconnected in at least two sets.

The present invention also provides a flat display screen including a cathode generating electrons bombarding a cathodoluminescent anode as mentioned above.

The foregoing objects, features and advantages of the present invention will be discussed in detail in the following non-limiting description of specific embodiments, in conjunction with the accompanying drawings.

Brief Description of the Drawings

Figs. 1, 2A and 2B, previously described, are meant to show the state of the art and the problem to solve;

Fig. 3 is a simplified partial cross-section view of a first embodiment of a flat display screen anode plate according to the present invention;

5 Figs. 4A and 4B very schematically and partially show, respectively in front view and in cross-section, a second embodiment of a flat screen anode according to the present invention more specifically intended for a screen having its surface formed by the cathode; and

10 Figs. 5A and 5B very schematically and partially show, respectively in front view and in cross-section, an alternative of the second embodiment of the present invention.

Detailed Description

The same elements have been referred to with the same references in the different drawings. For clarity, only those elements necessary to the understanding of the present invention
15 have been shown in the drawings and will be described hereafter. In particular, the structure of the cathode plate of a screen to which the present invention applies has not been detailed and is no an object of the present invention.

Fig. 3 shows a simplified cross-section view of a flat
20 display screen anode according to a first embodiment of the invention. This anode includes, as previously, a supporting plate 2, for example a glass plate. In the case of a screen observable from the anode, the plate is of course transparent.

Anode conductive strips 5R, 5G, 5B are deposited, for
25 example conventionally as illustrated in Figs. 2A and 2B, and are interconnected by sets of strips assigned to a same color.

A feature of the invention is that strips 5R, 5G, 5B, are covered with strips of a resistive material 8. According to the first embodiment of the present invention, strips of phosphor
30 elements 4R, 4G, 4B are then deposited on resistive strips 8 and no longer, as in conventional screens, directly on conductive strips 5. Thus, the biasing electrodes of the phosphor elements comprise a conductive layer (in which are defined strips 5R, 5G, 5B) and a resistive layer 8.

A significant advantage of the present invention is that it conforms with the conventional anode manufacturing method. Indeed, resistive layer 8 can, in the first embodiment, be deposited, at least in the active portion of the screen, that is, outside areas of interconnection of the strip sets, with the same pattern as anode conductive layers 5R, 5G, 5B, and thus by means of a same mask.

Another significant advantage of the present invention is that, while efficiently protecting the screen against destructive electric arcs, the present invention requires no increase of the lateral space between the strips of phosphor elements. The present invention thus is particularly well adapted to anodes of fine resolution.

Conventionally, anode strips 5R, 5G and 5B are preferably laterally separated by insulating interstitial strips 7.

It should be noted that the present invention enables protection against destructive electric arcs not only between the anode plate and the cathode plate, but also between neighboring strips of phosphor elements biased to different potentials. This lateral protection is particularly efficient since it acts against any current flow, even local.

Further, in case of an incidental misalignment of the etch masks used to deposit phosphor elements 4R, 4G, 4B with respect to the mask for forming anode conductive strips 5R, 5G, 5B, the material now accessible is the material of resistive layer 8, which prevents the forming of destructive electric arcs.

The choice of the material constitutive of resistive strips 8 depends on the application and, in particular, on the need for transparency (transparent anode) or for reflectiveness (transparent cathode) of the resistive strips.

As an example of choice of material to form resistive strips 8, tin oxide, or thin silicon, deposited with a thickness preferably ranging between one and two μm may be used. Conductive anode strips 5R, 5G, 5B are, for example, made of ITO (transpar-

ent) or aluminum (reflective) with a thickness on the order of one tenth of a μm .

It should be noted that the invention provides a significant improvement with respect to series ruthenium resistors that must have a thickness of several tens of μm .

Further, the first embodiment of the invention also applies to the case of a monochrome screen in which the anode is formed of a plane of phosphor elements of same color or to the case of a screen (color or monochrome) in which the anode is formed of several unswitched sets of strips. In this case, resistive layer 8 is, preferably, deposited over the entire anode conductive layer.

Although the anode according to the invention has been described in relation with a trichromatic structure with elongated anode strips parallel to one another in the first embodiment, the structure of the anode phosphor elements may be very different. For example, it may be a structure of elementary patterns, each of which corresponds to one pixel. In such a case, the present invention provides the additional advantage of being implementable while a lateral protection solution would take too much space.

Figs. 4A and 4B show, respectively in front view and in cross-section, a second embodiment of a flat screen anode according to the present invention. This embodiment is more specifically intended for an anode having to reflect the light towards the cathode plate (1, Fig. 1) that forms the screen surface.

A feature of the second embodiment of the invention is that the biasing electrodes of the phosphor elements are here formed of an arrangement of three layers. As in the first embodiment, a biasing conductive layer 5 and a resistive layer 8 are present. However, according to this second embodiment, an additional conductive layer 10 is deposited on the resistive layer. A feature of this additional layer 10 is to be reflective to reflect light towards the cathode. Thus, conversely to the first embodiment that, when implemented in a transparent cathode

screen, provides a reflective resistive layer, the second embodiment enables using a resistive layer having any optical properties (transparent, absorbing or reflective), the reflection towards the cathode being ensured by the additional conductive layer 10.

It should be noted that the second embodiment of the invention more specifically applies to the case where the phosphor elements are deposited in elementary patterns by means of a specific mask including openings, for example, corresponding to the respective sizes of the screen pixels or of the sub-pixels of each screen color. This feature is linked to the presence of conductive layer 10 that must itself be deposited according to the elementary patterns to avoid a charge propagation along the electrode strips.

Thus, as illustrated in Fig. 4A, phosphor elements 4'B, 4'R and 4'G are deposited according to elementary patterns (in this example, rectangular) having small surface areas. It should however be noted that, in the embodiment illustrated by Figs. 4A and 4B, the distribution of the colors of the phosphor elements is always performed along strips above the conductive biasing strips 5B, 5R, and 5G that are formed according to an alternated strip pattern.

According to this embodiment of the invention, the additional reflective conductive layer is deposited by means of the same mask as the phosphor elements and is thus formed of areas of elementary patterns 10 under the phosphor elements. An insulating layer 7 is optionally provided between the anode strips. Layer 7 is deposited, as in the first embodiment, on resistive layer 8'. However, when provided, insulating layer 7 is then present not only between the anode strips, but also between the different elementary patterns of definition of reflective layer areas 10 and phosphor element areas 4. It should be noted that the fact that the additional conductive layer is deposited according to the elementary patterns enables keeping a floating potential at each pixel.

In the embodiment illustrated in Figs. 4A and 4B, resistive layer 8' is deposited without being patterned, that is, it extends over at least the entire active area of the anode.

5 An advantage of the second embodiment of the invention is that it particularly well applies to a transparent cathode screen. Indeed, by dissociating the reflective layer and resistive layer functions, a wider choice of materials is available to form the different layers. In particular, a resistive layer 8' made of an optically absorbing material (for
10 example, silicon) can be provided. In this case, the resistive layer will then form a black matrix wherever there are no phosphor elements and no reflective layer 10. It will then absorb light, which improves the screen contrast.

Further, if the resistive layer is deposited without
15 being patterned, and if it is made of a material with a small secondary emission coefficient (which is generally the case for resistive materials), it will protect the underlying layer between conductive layers 5B, 5R, and 5G that is generally made of a material with a very high secondary emission coefficient,
20 and will then protect the anode against charge effects, which reduces the screen degassing.

As in the first embodiment, an advantage linked to the suppressing of the resistors at the ends of the anode conductive strips is, on the one hand, that space is gained on the anode,
25 but also that the thermal effects due to the presence of these resistors are distributed throughout the entire anode plate. Localized heating, which risks being prejudicial, is thus avoided.

Figs. 5A and 5B show, respectively in front view and in
30 cross-section, an alternative implementation of an anode according to the second embodiment of the invention. According to this alternative, resistive layer 8" is itself deposited according to the elementary patterns of deposition of phosphor elements 4'. For clarity, the alignment differences between the elementary
35 patterns of phosphor elements 4', of additional conductive layer

10, and of resistive layer 8" have been exaggerated in Figs. 5A and 5B. It should however be noted that these different elementary patterns are obtained by means of a same mask. Thus, the present invention remains compatible with conventional anode manufacturing methods and, in particular, requires no additional mask, whatever the embodiment used.

In the alternative of Figs. 5A and 5B, conductive biasing strips 5B, 5R, and 5G have still been shown in strips as in the first embodiment.

It should be noted that, as an alternative, the resistive layer provided in the second embodiment of the present invention may also be deposited according to the pattern of biasing conductive strips 5B, 5R, and 5G. In this case, the advantage of using no additional mask for the deposition of this resistive layer remains, as in the first embodiment.

In Fig. 5B, a resistive layer 8" relatively thicker than that illustrated in Fig. 4B has been shown. Indeed, according to the invention and whatever the embodiment, the value of the resistance can be adjusted according, for a given material, to the thickness of the deposited resistive layer.

Of course, the present invention is likely to have various alterations, modifications, and improvements which will readily occur to those skilled in the art. In particular, It should be noted that, in the case of a monochrome screen or of an unswitched anode screen, and as an application of the second embodiment of the present invention, biasing conductive layer 5 and resistive layer 8 may be deposited without being patterned. Reflective conductive layer 10 and the phosphor elements will then be deposited according to the elementary patterns of the screen pixels. Further, the choice of materials to form a flat screen anode according to the invention is within the abilities of those skilled in the art based on the functional indications given hereabove and on the applications. It should further be noted that those skilled in the art will easily adapt the thicknesses of the different layers and in particular of the

resistive layer according to the expected electric characteristics. Moreover, in the case of an unswitched anode, it should be noted that only the strips (or islands) of phosphor elements need individualizing in the active screen surface. Thus, biasing layer
5 5 may be a conductive plane and the resistive layer may not be patterned. There then is a single anode biasing electrode.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
22

CLAIMS

1. A flat display screen anode, including phosphor elements (4R, 4G, 4B; 4'R, 4'G, 4'B) intended for being excited by an electron bombardment, these elements being deposited on at least one biasing electrode including, at least under the phosphor elements, a resistive layer (8, 8', 8'') deposited on a conductive layer (5B, 5R, 5G) for biasing the phosphor elements.

2. The anode of claim 1, wherein the phosphor elements (4B, 4R, 4G) are directly deposited on the resistive layer (8).

3. The anode of claim 1, wherein the phosphor elements (4'B, 4'G, 4'R) are deposited on a reflective conductive layer (10), itself deposited on the resistive layer (8', 8'').

4. The anode of claim 3, wherein the reflective layer (10) is deposited according to elementary patterns of small dimension in the anode surface.

5. The anode of claim 4, wherein the phosphor elements (4'B, 4'R, 4'G) are deposited according to the elementary pattern of deposition of the reflective layer (10).

6. The anode of any of claims 1 to 5, wherein the resistive layer (8, 8', 8'') is not patterned.

7. The anode of any of claims 3 to 5, wherein the resistive layer (8'') has the same pattern as the reflective layer (10).

8. The anode of any of claims 1 to 7, wherein the resistive layer (8) has, at least in the active screen area, the same pattern as the biasing conductive layer (5).

9. The anode of any of claims 1 to 8, wherein said conductive layer has a pattern of alternate strips (5R, 5G, 5B) interconnected in at least two sets.

10. A flat display screen including a cathode (1) for generating electrons bombarding the cathodoluminescent anode (2) of claim 1.

FLAT DISPLAY SCREEN RESISTIVE ANODE

Abstract

A flat display screen anode, including phosphor elements intended for being excited by an electron bombarding, these elements being deposited on at least one biasing electrode including, at least under the phosphor elements, a resistive layer deposited on a conductive layer for biasing the phosphor elements.




Fig 1




Fig 2A




Fig 2B




Fig 3




Fig 4A




Fig 4B




Fig 5A




Fig 5B

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Attorney Docket Number	Banca1-8
	First Named Inventor	Banca1
	COMPLETE IF KNOWN	
	Application Number	/ Herewith
	Filing Date	Herewith
	Group Art Unit	TBA
	Examiner Name	TBA

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

FLAT DISPLAY SCREEN RESISTIVE ANODE

the specification of which *(Title of the Invention)*

☒ is attached hereto
OR
☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
99 02654	FR	2/26/99	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)
<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.	

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box →



PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number
Arthur L. Plevy	24,277	Jonathan M. Darcy	44,054
Edward J. Howard	42,670	Paul A. Schwarz	37,577

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label OR ☒ Correspondence address below

Name	Arthur L. Plevy; BUCHANAN INGERSOLL, P.C.				
Address	650 College Road East, 4th Floor				
Address					
City	Princeton	State	NJ	ZIP	08540
Country	US	Telephone	609-987-6880	Fax	609-520-0360

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])		Family Name or Surname			
Bernard		Bancal			
Inventor's Signature				Date	
Residence: City	Luynes	State		Country	FR
Post Office Address	5, Allée de Lodena				
Post Office Address					
City	Luynes	State		ZIP	13080
				Country	France

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → +

PTO/SB/02A (3-97)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet

Page 1 of 1

Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name (first and middle [if any])				Family Name or Surname				
Pascal				Olivier				
Inventor's Signature					Date			
Residence: City		Montpellier	State		Country	FR	Citizenship	FR
Post Office Address		3, Rue Chamaillou						
Post Office Address								
City		Montpellier	State		ZIP	34000	Country	France
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name (first and middle [if any])				Family Name or Surname				
Inventor's Signature					Date			
Residence: City			State		Country		Citizenship	
Post Office Address								
Post Office Address								
City			State		ZIP		Country	
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor				
Given Name (first and middle [if any])				Family Name or Surname				
Inventor's Signature					Date			
Residence: City			State		Country		Citizenship	
Post Office Address								
Post Office Address								
City			State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.